

GUANTE PVC JUBA - PM3P214 JUBA

Guante sin costuras de Nylon®/algodón con puntos de PVC en la palma



NORMATIVA



ESPECIALES

GUANTES DE TRABAJO RECOMENDADOS PARA:

- Inspección de calidad.
- Logística y transporte.
- Operaciones mecánicas ligeras.
- Reponedores.

CARACTERÍSTICAS

- Ergonómico.
- Nylon® exterior para mayor resistencia a la abrasión y algodón interior para mayor confort y calidez .
- No desprende pelusa.
- Mayor agarre y resistencia a la abrasión por los puntos de PVC.
- Color oscuro para trabajos en ambientes más sucios.

Nylon® / Algodón

código	acabado	color	grueso	largo	talla	embalaje
					S -	
					23cm	
					M -	S/7 12
PM3P- Liso con					24cm	M/8 pares/paquete
214	puntos PVC	Azul	Galga	13	L -	L/9 300
					25cm	XL/10 pares/caja
					XL -	
					26 cm	

MÁS INFORMACIÓN

Materiales	Color	Grueso	Largo	Tallas	Embalaje
Pvc	Azul	Galga 13	S - 23 cm M - 24 cm L - 25 cm XL - 26 cm	7/S 8/M 9/L 10/XL	12 pares/paquete 240 pares/caja

NORMATIVAS


EN388:2016



EN388:2016 Protective gloves against mechanical risks.

The EN388: 2003 standard is renamed EN388: 2016, the year of its revision. The reason for the modification is given by the discrepancies in the results between laboratories in the knife cut test, COUP TEST. Materials with high levels of cut produce a dulling effect on the circular blades, which undermines the result.

The new regulation was published in November 2016 and the previous one is from the year 2003. During these 13 years, there has been a great innovation in the materials for the manufacture of cutting gloves, they have forced to introduce changes in the tests to be able to measure with more rigorous levels of protection. If you want to know more about the main changes in these regulations, you can consult it through our website www.iubappe.es



- A - Abrasion resistance (X, 0, 1, 2, 3, 4)
- B - Blade Cut Resistance (X, 0, 1, 2, 3, 4, 5)
- C - Tear resistance (X, 0, 1, 2, 3, 4)
- D - Puncture resistance (X, 0, 1, 2, 3, 4)
- E - Cutting by sharp objects ISO 13997 (A, B, C, D, E, F)
- F - Impact test complies / does not comply (It is optional. If it complies, put P)

En388:2016 performance levels	1	2	3	4	5
6.1 abrasion resistance (cycles)	100	500	2000	8000	-
6.2 blade cut resistance (index)	1,2	2,5	5	10	20
6.4 tear resistance (newtons)	10	25	50	75	-
6.5 puncture resistance (newtons)	20	60	100	150	-

Eniso13997:1999 performance levels	A	B	C	D	E	F
6.3 tdm: cut resistance (newtons)	2	5	10	15	22	30