

GUANTE - B271VRIZDA VIBRA-MCX

Guante de piel sintética en palma con dorso de elastano, con protección Gelfom® anti-vibración en palma y dedos



NORMATIVA



ESPECIALES

GUANTES DE TRABAJO RECOMENDADOS PARA:

- Trabajos con vibraciones no agresivas

CARACTERÍSTICAS

- Especial vibraciones.
- Protección anti-vibración en palma y dedos.
- Acolchado en nudillos para una protección adicional.
- Cierre con velcro para mayor ajuste.
- Se vende por unidad, mano derecha o mano izquierda.
- Flexible, cómodo y transpirable.
- Con bolsa individual para punto de venta.

Vibra-Mecanix®
códigoacabado

color	largo	talla	embalaje
		M/8-	
		mano derecha	
		o	
		M/8-	

B271 VR
 Cuero sintético/Elastano (Spandex)
 Interior forro Gelfom™
 Negro
 8-26,5cm mano izquierda
 9-27,5cm mano derecha
 10-28,5cm mano izquierda
 XL/10-
 mano derecha
 o
 XL/10-
 mano izquierda

MÁS INFORMACIÓN

Materiales	Color	Largo	Tallas	Embalaje
Piel Sintética	Negro	M - 26 cm L - 27 cm XL - 28 cm	8/M 9/L 10/XL 11/XXL	1 unidad/paquete 50 unidades/caja

NORMATIVAS


EN388:2016



EN388:2016 Protective gloves against mechanical risks.

The EN388: 2003 standard is renamed EN388: 2016, the year of its revision. The reason for the modification is given by the discrepancies in the results between laboratories in the knife cut test, COUP TEST. Materials with high levels of cut produce a dulling effect on the circular blades, which undermines the result.

The new regulation was published in November 2016 and the previous one is from the year 2003. During these 13 years, there has been a great innovation in the materials for the manufacture of cutting gloves, they have forced to introduce changes in the tests to be able to measure with more rigorous levels of protection. If you want to know more about the main changes in these regulations, you can consult it through our website www.jubappe.es



- A - Abrasion resistance (X, 0, 1, 2, 3, 4)
- B - Blade Cut Resistance (X, 0, 1, 2, 3, 4, 5)
- C - Tear resistance (X, 0, 1, 2, 3, 4)
- D - Puncture resistance (X, 0, 1, 2, 3, 4)
- E - Cutting by sharp objects ISO 13997 (A, B, C, D, E, F)
- F - Impact test complies / does not comply (It is optional. If it complies, put P)

En388:2016 performance levels	1	2	3	4	5
6.1 abrasion resistance (cycles)	100	500	2000	8000	-
6.2 blade cut resistance (index)	1,2	2,5	5	10	20
6.4 tear resistance (newtons)	10	25	50	75	-
6.5 puncture resistance (newtons)	20	60	100	150	-

Eniso13997:1999 performance levels	A	B	C	D	E	F
6.3 tdm: cut resistance (newtons)	2	5	10	15	22	30