

GUANTE PVC JUBA - 5130W ICE BLUE

Guante sin costuras de Nylon® con interior vulvizo recubierto en palma de PVC con tratamiento HPT. Especial para bajas temperaturas.



NORMATIVA



ESPECIALES

GUANTES DE TRABAJO RECOMENDADOS PARA:

- Reponedores zona frío.
- Trabajos exteriores.
- Cámaras frigoríficas y congelado.
- Construcción.
- Carretilleros.
- Manipulación de alimentos congelados.
- Transporte de mercancía refrigerada.
- Agricultura.

CARACTERÍSTICAS

- Interior con acabado vulvizo que mantiene la temperatura estable de las manos en situaciones con temperatura hasta 0°C.
- Recubierto de PVC con tecnología HPT (Hydropellent Technology) que repele los líquidos y facilita el agarre en medios húmedos y secos.
- Gran resistencia y muy duradero.
- Ofrece una buena flexibilidad y confort.
- Apto para uso alimentario.

PVC/NYLON®
código/acabado

color

grueso/largo/talla embalaje

5130 W Recubrimiento palma PVC con HPT Azul/Negro Galga 15

XS - 22 cm
 S - 23 cm
 M - 24 cm
 L - 25 cm
 XL - 26 cm

XS/6
 S/7 6
 M/8 pares/paquete
 L/9 72 pares/caja
 XL/10

MÁS INFORMACIÓN

Materiales	Color	Grueso	Largo	Tallas	Embalaje
Pvc	Negro / Azul	Galga 15	XS - 22 cm S - 23 cm M - 24 cm L - 25 cm XL - 26 cm XXL - 27 cm	6/XS 7/S 8/M 9/L 10/XL 11/XXL	6 pares/paquete 72 pares/caja

NORMATIVAS


EN388:2016



EN388:2016 Protective gloves against mechanical risks.

The EN388: 2003 standard is renamed EN388: 2016, the year of its revision. The reason for the modification is given by the discrepancies in the results between laboratories in the knife cut test, COUP TEST. Materials with high levels of cut produce a dulling effect on the circular blades, which undermines the result.

The new regulation was published in November 2016 and the previous one is from the year 2003. During these 13 years, there has been a great innovation in the materials for the manufacture of cutting gloves, they have forced to introduce changes in the tests to be able to measure with more rigorous levels of protection. If you want to know more about the main changes in these regulations, you can consult it through our website www.jubappe.es



- A - Abrasion resistance (X, 0, 1, 2, 3, 4)
- B - Blade Cut Resistance (X, 0, 1, 2, 3, 4, 5)
- C - Tear resistance (X, 0, 1, 2, 3, 4)
- D - Puncture resistance (X, 0, 1, 2, 3, 4)
- E - Cutting by sharp objects ISO 13997 (A, B, C, D, E, F)
- F - Impact test complies / does not comply (It is optional. If it complies, put P)

EN388:2016 performance levels	1	2	3	4	5
6.1 abrasion resistance (cycles)	100	500	2000	8000	-
6.2 blade cut resistance (index)	1,2	2,5	5	10	20
6.4 tear resistance (newtons)	10	25	50	75	-
6.5 puncture resistance (newtons)	20	60	100	150	-

Eniso13997:1999 performance levels	A	B	C	D	E	F
6.3 tdm: cut resistance (newtons)	2	5	10	15	22	30

EN511



EN 511:2006



Levels vs temperature of glove use

- If the convective cold is level 0 - This glove can be used up to a temperature of 0°C
- If the convective cold is level 1 - This glove can be used up to a temperature of -10°C
- If the convective cold is level 2 - This glove can be used up to a temperature -20°C
- If the convective cold is level 3 - This glove can be used up to a temperature of -30°C
- If the convective cold is level 4 - This glove can be used up to a temperature of -40°C

Gloves on both hands must meet the requirements below:

Performance level	1	2	3	4
A convective cold resistance*	ltr thermal insulation in m ² c/w itr ≤ 0,15	0,10 ≤ itr ≤ 0,22	0,15 ≤ itr ≤ 0,30	0,22 ≤ itr ≤ 0,30
B contact cold resistance	Thermal resistance r in m ² c/w r ≤ 0,050	0,025 ≤ r ≤ 0,100	0,050 ≤ r ≤ 0,150	0,100 ≤ r ≤ 0,150
C water impermeability	Waterproof for at least 30 minutes	Pass		