

Powercap® Active IP (anti-impact) prise internationale

Noir / CAE602-941-100



DESCRIPTION

La PowerCap® Active™ est un appareil respiratoire léger à pression positive avec protection des yeux et du visage contre les chocs et protection par casquette anti-heurt EN812. Léger, solide et ergonomique, la PowerCap® Active™ est conçue pour protéger l'utilisateur de la poussière et de la plupart des particules polluantes en suspension dans l'air selon la norme EN12941 TH1P.

- Visière en polycarbonate de 1 mm d'épaisseur avec bords en aluminium assurant une protection contre les chocs - fixée par des rivets.

OPTIONS

Noir (CAE602-941-100)

NORMES

EN 12941 • EN 812 • EN 166



INFORMATIONS TECHNIQUES



Visière
7cm



Résistance aux chocs latéraux
12 Joules



Température Minimale
+5°C



Recyclable
Calotte:



Ventilation
Oui

Classification
TH1 (Turbo Hood)

Utilisation
R (Réutilisable)

Efficacité de filtration minimale
90%

Facteur nominal de protection
10

Conception des masques
EPR a ventilation assistée avec cagoule ou casque
- sans ajustement étanche nécessaire

Sans latex
Oui

Durée de stockage des filtres
5 ans

Type de batterie
Lithium-ion rechargeable 2 x 3,7v 1,9Ah



Classe optique (1 - Classe 1- qualité élevée pour le port permanent. 2 - Classe 2 – qualité moyenne pour le port intermittent. 3 – Classe 3 – qualité faible pour des travaux occasionnels et de courte durée).
1



Protection contre les projections de liquides
3



Poids du produit
659g



Résistance à l'impact
12 Joules x 4



Température Maximale
-40°C



Calotte PEHD
Oui



Serrage glissière
Glissière



Option réfléchissante
Non



Type de filtre
P (protection contre les aérosols solides et liquides)



Valve d'expiration
Non

Fuite totale vers l'intérieur (TIL)
10% lorsqu'ils sont montés sur l'équipement de ventilation assistée PowerCap® Active™

Facteur de protection assigné au Royaume-Uni
10

Type de joint facial
Matériau hypoallergénique

Sans métal
Non

Matériau filtre
Média filtrant plissé



Marque du fabricant
Dague JSP



Impact à moyenne énergie, résiste à une bille de 6 mm, de 0.86g tombant à 120 m/s. Protection maximale les lunettes masques de sécurité.
B



BSI Kitemark
Oui

Niveau sonore
68.2dB

CARACTÉRISTIQUES



Powered Air

Protection to EN 12941 TH1P provides a cooling, comfortable supply of filtered air at 160 litres per minute, eliminating breathing resistance and visor misting.



Casquette anti-heurts

The cap uses JSP HardCap™ A1+ bump cap technology, exceeding the EN 812 standard. The cap cover is easily removable, wipeable and machine washable.



JSP Limited, Worsham Mill, Minster Lovell, Oxford OX29 0TA, England.

Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: sales@jpsafety.com / Web: www.jpsafety.com

Do Not Publish without written permission from JSP Limited. Contact copyright@jpsafety.com. Information correct in the United Kingdom at date of issue and may be subject to change. Any third-party machine and automated translations processed by users may have inaccuracies and should not be relied upon.

Page 2 of 3 / Issued 24 Apr 2025 / Copyright 2018 - 2025. JSP Limited. All Rights Reserved.





Micro USB Charging

PowerCap® Active™ is supplied with a micro USB cable for recharging in as little as 5 hours. The PowerBox™1 battery pack features a built-in fuel gauge, making it easy to check charge level.



Protection des yeux et du visage

The IP version offers eye and face impact protection to EN 166 1 B, ideal for working in environments where there is a danger of flying particles. Film pelables disponibles.

GAMME



VIDÉOS

 www.jspgo.com/UI-FH/UI_PowercapActive/UI_PowercapActive

TÉLÉCHARGEMENTS

 [Pack d'images \(ZIP\)](#)

 [doc-powercap_active_ip.pdf \(PDF\)](#)



JSP Limited. Worsham Mill. Minster Lovell. Oxford OX29 0TA. England.

Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: sales@jspgo.com / Web: www.jspgo.com

Do Not Publish without written permission from JSP Limited. Contact copyright@jspgo.com. Information correct in the United Kingdom at date of issue and may be subject to change. Any third-party machine and automated translations processed by users may have inaccuracies and should not be relied upon.

Page 3 of 3 / Issued 24 Apr 2025 / Copyright 2018 - 2025. JSP Limited. All Rights Reserved.

